UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/597,339	09/06/2006	Nicholas Richard Pennance	06099	9482
DENNISON, SCHULTZ & MACDONALD 1727 KING STREET SUITE 105 ALEXANDRIA, VA 22314			EXAMINER	
			BARON, HENRY	
			ART UNIT	PAPER NUMBER
			2462	
			MAIL DATE	DELIVERY MODE
			02/15/2011	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
Office Action Summary	10/597,339	PENNANCE, NICHOLAS RICHARD			
omeo nenem cammary	Examiner	Art Unit			
	HENRY BARON	2462			
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 16(a). In no event, however, may a reply be tim ill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONEI	lely filed the mailing date of this communication. (35 U.S.C. § 133).			
Status					
 1) Responsive to communication(s) filed on 11/22 2a) This action is FINAL. 2b) This 3) Since this application is in condition for allowant closed in accordance with the practice under E 	action is non-final. ace except for formal matters, pro				
Disposition of Claims					
4) ☑ Claim(s) <u>1-9</u> is/are pending in the application. 4a) Of the above claim(s) _ is/are withdrawn from 5) ☐ Claim(s) is/are allowed. 6) ☑ Claim(s) <u>1-9</u> is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or					
Application Papers					
9) The specification is objected to by the Examiner 10) The drawing(s) filed on is/are: a) access Applicant may not request that any objection to the of Replacement drawing sheet(s) including the correction of the original transformation are objected to by the Examiner 11) The oath or declaration is objected to by the Examiner	epted or b) \square objected to by the Edrawing(s) be held in abeyance. See on is required if the drawing(s) is obj	e 37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 					
Attachment(s) 1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413)					
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 	4)	ate			

Application/Control Number: 10/597,339 Page 2

Art Unit: 2462

Detailed Action

EXTENDING THE RANGE OF A HAND-PORTABLE RADIO

Response to Arguments/Remarks

- 1. Claims 1-9 are pending in the application.
- 2. Claims 1, 6, and 9 have been amended;
- 3. Applicant's arguments filed 11/22/2011 have been fully considered but they are not persuasive.
- 4. The Applicant articulates that the invention obviates the need for an additional piece of equipment in a vehicle, by programming the on-board station to take the place of a repeater and when the portable is out of range of the network, the on-board station receives messages from the portable over a half duplex channel, and transmits the messages to the network over a different radio channel
- 5. By contrast, Applicant argues that the problem solved by the primary 103 reference is the inability of the subscriber unit to receive signals from the repeater which is solved by having a higher powered store and forward repeater, which operates on the same frequency as the subscriber unit. Dinkins, Applicant argues, discloses that store and forward repeater units are known, but does not disclose or suggest programming an on-board radio to act as a store and forward repeater unit when a hand portable is out of range of a network. Further, Applicant argues that Dinkins assumes that the subscriber unit can always transmit to the network through the remote receivers, but cannot always receive; contrary to what is assumed of the invention's hand portables.

Application/Control Number: 10/597,339 Page 3

Art Unit: 2462

6. Applicant argues that Lee discloses office computer equipment rather than radio stations that are linked by infrared and do not form part of a mobile radio network and further, Lee's repeater stations are dedicated hardware, rather than user-operated stations. Applicant argues that a person skilled in the art of mobile radio would consider the Dinkins patent, but the Lee et al patent relates to a different area of technology, and there would not be any reason to combine the references.

7. Examiner replies that in the 35 USC § 103 rejection, Dinkins was relied on a system and method for mobile radio communication, including: a network having one or more radio base stations, a central station, an on-board radio station having a relatively long range for communication with other stations which corresponds to a having a higher powered store and forward repeater. Claim 1 does not call for programming an on-board radio. Lee is relied to complement Dinkins to teach of infrared signal communication over the same channel which is inherently half duplex channel. Office computer equipment that communicate over the infra-red electromagnetic wave band, like radio stations are communication devices and can be portable. Further, Examiner notes that the term 'on-board' is very broad (on board what?)

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - a. A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1. 6, and 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Dinkins, (U.S. Patent (5,633,876), in view of Lee et al (U.S. Patent 5099346) hereafter Lee.

Art Unit: 2462

3. With regards to claims 1, 6, and 9, Dinkins teaches a system and method for mobile radio communication, including: a network having one or more radio base stations and a central station; (3: [0032] read As shown in FIG. 2, store and forward repeater 22 includes a receiver 24, memory 26, controller 28, transmitter 30, and power supply 32. In the present embodiment, local base station repeater cell i.e. one or more radio base stations broadcasts data signals on an rf carrier frequency i.e. a central station) user operated on-board radio station having a relatively long range for communication with other stations; (3: [0034] read With reference next to FIG. 2, a communication system including a store and forward repeater 22 for relaying data signals between a local base station repeater cell 10 i.e. on-board radio station having a relatively long range for communication with other stations and a subscriber unit 12 is shown.) where the on-board station receives messages from the portable station when the on-board station is within range of the network but the portable station is out of range of the network; stores the messages and forwards the messages to the network over a different radio channel. (4: [0007] read [I]n the present embodiment, the receiver of subscriber unit 12 is tuned to receive data signals broadcast from store and forward repeater 22 i.e. on-board station on an rf carrier in the range of approximately 218-219 MHz. Thus, in the present embodiment, the frequency of the rf carrier used to transmit data signals from local base station repeater cell 10 to store and forward repeater 22 is the same as the frequency of the rf carrier used to transmit data signals from store and forward repeater 22 to subscriber unit 12. However, in order for the same carrier frequency to be used in link 11 and link 23, any data signals broadcast from local base station repeater cell 10 must be extremely weak, for example less than 95 dBm, at subscriber unit 12 i.e when the on-board station is within range of the network but the portable station is out of range of the network AND stores the messages and forwards the messages to the network over a different radio channel. If data signals broadcast from local base station repeater cell 10 are not extremely weak, subscriber unit 12 can receive data signals from both local base station repeater cell 10 and store and forward repeater 22.).

- 4. Dinkins does not disclose where the on-board station receives messages from the portable station over a half duplex channel.
- 5. Lee teaches (see Abstract) of an infrared data communications network in which groups of personal computers and associated peripherals may communicate by infrared signals with each other <u>i.e.</u> where the on-board station receives messages from the portable station over a half duplex channel.

 NOTE; infrared signal communication over the same channel is inherently half duplex channel.
- 6. It would have been obvious at the time the invention was made by a person of to having ordinary skill in the art to modify the teachings of Dinkins with the teachings of Lee.
- 7. In this manner, a low power and low cost, half duplex mobile unit can communicate to a base station using a higher power, but economical store and forward repeater, forming a useful and dynamic system.
- 8. Claims 2 3, 5, 7 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Dinkins, (U.S. Patent (5,633,876), in view of Lee et al (U.S. Patent 5099346) hereafter Lee and in further view of Mulford (U.S. Patent 5768683)
- 9. In regards to claims 2 and 8, Dinkins modified teaches of a system wherein the on-board station receives and forwards messages from the portable station to the central station. (3: [0032] read As shown in FIG. 2, store and forward repeater 22 includes a receiver 24, memory 26, controller 28, transmitter 30, and power supply 32. In the present embodiment, local base station repeater cell <u>i.e.</u> one or more radio <u>base stations</u> broadcasts data signals on an rf carrier frequency <u>i.e.</u> a central station .. and 3: [0034] read With reference next to FIG. 2, a communication system including a store and forward repeater 22 for relaying data signals between a local base station repeater cell 10 <u>i.e.</u> on-board radio station having a relatively long range for communication with other stations and a subscriber unit 12 is shown.).
- 10. Dinkins does not disclose of emergency messages per se.

- 11. Mulford teaches where the on-board station receives and forwards emergency messages from the portable station to the central station. (6:[0023] read When the mobile is associated with the portable, the special condition indicator is detected in the voice message at step 402. In a preferred embodiment, the special condition indicator is used to indicate the occurrence of an emergency situation <u>i.e. on-board station receives and forwards emergency messages</u>, as would typically be required in public safety systems, e.g., police and fire departments. It is understood that a special condition indicator could be used to specify any of a number of circumstances as required by a particular system <u>i.e. on-board station receives and forwards.</u>)
- 12. It would have been obvious at the time the invention was made by a person of to having ordinary skill in the art to modify the teachings of Dinkins with the teachings of Lee and Mulford.
- 13. In this manner, in an emergency situation, a mobile user can communicate with a remote user for emergency assistance.
- 14. With respect to claim 3, Dinkins modified, teaches the limitations of claim 1, but does not disclose of a system where the portable station and the on-board station communicate messages in either direction over a half-duplex radio channel
- 15. Lee teaches of infra-red channel communications that are inherently half-duplex, but does not disclose of short data messages or voice messages.
- 16. Mulford teaches of where voice messages may be transmitted over the on-board station receives and forwards voice messages (Abstract; A digital voice message, including a continuously embedded portable identification code, is transmitted by a portable communication unit (105) to a mobile communication unit (104) and to broadcast units (101-103). i.e the on-board station receives and forwards voice messages).
- 17. It would have been obvious at the time the invention was made by a person of to having ordinary skill in the art to modify the teachings of Dinkins with the teachings of Lee and Mulford.

- 18. In this manner, in a non-emergency situation, a mobile user can communicate with a remote user providing status information using either voice or data messages.
- 19. In consideration of claim 5, Dinkins teaches where the on-board station and the portable station are wireless, mobile devices where the portable station is associated with the on-board station. (3: [0032] read With reference next to FIG. 2, a communication system including a store and forward repeater 22 for relaying data signals between a local base station repeater cell 10 and a subscriber unit 12 is shown. As shown in FIG. 2, store and forward repeater 22 includes a receiver 24, memory 26, controller 28, transmitter 30, and power supply 32. In the present embodiment, local base station repeater cell 10 broadcasts data signals on an rf carrier frequency. The rf link between local base station repeater cell 10 and store and forward repeater 22 is shown as link 11. The data signals are received by receiver 24 of store and forward repeater 22. Receiver 24 is tuned to the rf carrier frequency of local base station repeater cell 10. In the present embodiment, receiver 24 is tuned to receive rf transmissions in the range of approximately 218-219 MHz. Although receiver 24 is tuned to approximately 218-219 MHz in the present embodiment, the present invention is also well suited to having receiver 24 tuned to other frequencies matching the transmission frequency of local base station repeater cell 10. Store and forward repeater 22 stores the data signals in memory 26.)
- 20. Dinkins does not disclose where the on-board station is carried by a vehicle and the portable station is carried by an individual associated with the vehicle.
- 21. Mulford teaches where the on-board station is carried by a vehicle and the portable station is carried by an individual associated with the vehicle (6:[0023] read When the mobile is associated with the portable, the special condition indicator is detected in the voice message at step 402. In a preferred embodiment, the special condition indicator is used to indicate the occurrence of an emergency situation i.e. on-board station receives and forwards emergency messages, as would typically be required in public safety systems, e.g., police and fire departments. It is understood that a special condition indicator could

be used to specify any of a number of circumstances as required by a particular system <u>i.e.</u> <u>on-board</u> station receives and forwards. i.e. the on-board station is carried by a vehicle and the portable station is carried by an individual associated with the vehicle.)

- 22. It would have been obvious at the time the invention was made by a person of to having ordinary skill in the art to modify the teachings of Dinkins modified in this manner, so that the wireless device can communicate with a base station using a store and forward repeater freeing the mobile user from carrying a bulky communication device.
- 23. Regarding claim 7, Dinkins teaches wherein the on-board station receives messages from the portable station on one channel and transmits the messages on a different channel. (4: [0057] read In another embodiment of the present invention, in instances where data signals broadcast from local base station repeater cell 10 are not extremely weak at each of the respective receiving subscriber units, the frequency of the rf carrier used to transmit data signals from local base station repeater cell 10 to store and forward repeater 22 is different than the frequency of the rf carrier used to transmit data signals from store and forward repeater 22 to subscriber unit 12. That is, link 11 has a different carrier frequency than link 23. In such an embodiment, subscriber unit 12 is tuned to the frequency of the of the rf carrier transmitted from store and forward repeater 22 i.e. the on-board station receives messages from the portable station on one channel and transmits the messages on a different channel.)
- 24. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Dinkins, (U.S. Patent (5,633,876), in view of Lee et al (U.S. Patent 5099346) hereafter Lee, in further view of Mulford (U.S. Patent 5768683), and in further view of Proctor (U.S. Patent Application 20060183421).
- 25. With respect to claim 4, Dinkins modified teaches the limitations of claim 1 in particular of half duplex mobile unit to store and forward repeater communication, but fails to disclose where the portable and on-board stations each have a duplex mode for communication with the network by data and a half-duplex mode for communication between each other by messages.

Art Unit: 2462

- 26. Proctor teaches of a multimode (duplex and half-duplex) communications where the portable and on-board stations each have a duplex mode for communication with the network by data and a half-duplex mode for communication between each other by messages. (5: [0041] read [T]o appreciate the operation of the physical layer repeater 200, two scenarios 210 and 220 are shown in FIGS. 2A, 2B, (full duplex) 2C and 2D (half duplex). In a pure PHY layer mode of operation, as shown in scenario 210, a configuration 211 is shown in FIG. 2A where a signal is received on a first frequency F1 and repeated on a second frequency F2. The flow diagram 212 of FIG. 2B shows that the packets are essentially received and transmitted at the same time (full duplex). A non-physical layer repeater configuration 221 is shown in FIG. 2C including repeater sections for transmitting and receiving on the same frequency F1 i.e. half duplex. On the receive side, the baseband processing and MAC processing are conducted and, for example, address information is extracted and stored.)
- 27. It would have been obvious at the time the invention was made by a person of to having ordinary skill in the art to modify the teachings of Dinkins modified with the teachings of Proctor.
- 28. In this manner, a multimode (duplex and half-duplex) communications link where a portable and on-board stations each depending on channel conditions and attributes of the message.

FINAL ACTION

- 1. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).
 - a. A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37

Application/Control Number: 10/597,339 Page 10

Art Unit: 2462

CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event,

however, will the statutory period for reply expire later than SIX MONTHS from the date of this

final action

Conclusion

29. Any inquiry concerning this communication or earlier communications from the examiner should

be directed to HENRY BARON whose telephone number is (571)270-1748. The examiner can normally

be reached on 7:30 AM to 5:00 PM E.S.T. Monday to Friday.

30. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor,

Seema Rao can be reached on (571) 272-3174. The fax phone number for the organization where this

application or proceeding is assigned is 571-273-8300.

31. Information regarding the status of an application may be obtained from the Patent Application

Information Retrieval (PAIR) system. Status information for published applications may be obtained

from either Private PAIR or Public PAIR. Status information for unpublished applications is available

through Private PAIR only. For more information about the PAIR system, see http://pair-

direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer

Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR

CANADA) or 571-272-1000.

/H. B./ Examiner, Art Unit 2462

HIB